

DALLAS, TX
DART

40’ LOW FLOOR CNG

GILLIG
COMPRESSED NATURAL GAS

www.GILLIG.com

VEHICLE SPECIFICATIONS

CUSTOMER CONFIGURATION

STRUCTURE

BODY	Bolted extruded aluminum
CHASSIS	3CR12 stainless steel w/ integrated side-impact barriers
STYLING PACKAGE	Low Floor
WINDOWS	Arow Global framed, full fixed
FLOORING	Altro Chroma™
EXTERIOR MIRRORS	Safe Fleet 8” x 15” 2-piece flat & convex
BIKE RACK	Sportworks® Apex+ 2™

POWERTRAIN

ENGINE	Cummins L9N™
TRANSMISSION	Allison B400R w/ retarder
COOLING	Modine® E-Fan
ALTERNATOR	EMP P450, 450 amp
BATTERIES	Odyssey® Extreme Series™ AGM
FUEL TANKS	(5) Type 4, 148.5”
FUEL FILL	Sherex 5000 Series fast-fill port
AIR DRYER	SKF® HC Dual Turbo-2000
FIRE SUPPRESSION	Amerex SafetyNet V-25

CHASSIS

AXLES	Meritor®
BRAKES	EX+™ Disc
STEERING	TRW® TAS6505 w/ JTEKT single tilt
WHEELS	Accuride white powder-coated steel
TIRES	Firestone® 315/80R22.5

PASSENGER

FRONT DOOR	40” Vapor Ameriview® Slide-Glide
REAR DOOR	34” Vapor Ameriview® Swing-Out
DOOR OPERATION	5-Position Vapor Analog Controller
PASSENGER SEATS	STER Aries
ADA RESTRAINTS	Q’Straint® Q’POD®
RAMP	Lift-U® Dual-Mode
HVAC	Thermo King T14 w/ X430 compressor
INTERIOR LAMPS	I/O Controls LED

DRIVER

DRIVER’S SEAT	Ergo Metro AM384
DRIVER’S BARRIER	Arow Global ArowGuard MAX
PEDALS	Kongsberg adjustable throttle & brake
STOP REQUEST	Pull cords
DASH DISPLAY	I/O Controls MFD 2 multi-function display
HEADLAMPS	Dialight LED low & high beam

ELECTRONICS

DESTINATION SIGNS	Hanover® white
PASSENGER INFO	Message Point Media w/ (2) 37” monitors
VIDEO SURVEILLANCE	Genetec 7-camera system w/ Streamvault™ recorder
APC	UTA w/ Xovis APS-B vertical sensing
IT SYSTEM	Vontas OnRoute™

Specifications reflect the DART configuration and are subject to change.