

ARLINGTON HEIGHTS, IL
PACE

35’ LOW FLOOR PLUS HYBRID

GILLIG HYBRID

www.GILLIG.com

VEHICLE SPECIFICATIONS

CUSTOMER CONFIGURATION

STRUCTURE

BODY	Bolted extruded aluminum
CHASSIS	3CR12 stainless steel w/ integrated side-impact barriers
STYLING PACKAGE	Low Floor Plus
WINDOWS	Arow Global bonded transom
FLOORING	Altro
EXTERIOR MIRRORS	Safe Fleet 8” x 15”
BIKE RACK	Sportworks® VeloPorter 2™

POWERTRAIN

ENGINE	Cummins B6.7™
TRANSMISSION	Allison eGen Flex™ 40 Max
COOLING	Modine® Gen III E-Fan
ALTERNATOR	(2) Vanner® Hybrid Beltless Alternator® (HBA®)
BATTERIES	Odyssey® AGM
FUEL TANK	3CR12 stainless steel, 120-gal. capacity
FUEL FILL	Emco Wheaton Posi-Lock
AIR DRYER	Bendix® single AD-IP®
FIRE SUPPRESSION	Amerex V-25

CHASSIS

AXLES	Meritor®
BRAKES	Disc
STEERING	TRW® TAS6505 w/ JTEKT single tilt column
WHEELS	Alcoa® aluminum w/ Dura-Bright® EVO finish
TIRES	Michelin® 305/85R22.5

CLIMATE

HVAC	Thermo King TE14 all-electric
AUX. COOLANT HEATER	Dometic X30
DOOR THRESHOLD HEATERS	(2) Bus Climate Control, 12K BTU
STREET-SIDE FLOOR HEATER	Bus Climate Control, 12K BTU

PASSENGER

FRONT DOOR	40” VaporAmeriview® Slide-Glide, air open/close
REAR DOOR	48” VaporAmeriview® Slide-Glide w/ Vapor CLASS®
DOOR OPERATION	Vapor analog controller
PASSENGER SEATS	American Seating InSight-Prime+®
ADA RESTRAINTS	Q’Straint® Q’POD® & Quantum®
RAMP	Lift-U® LU18
INTERIOR LAMPS	Pretoria

DRIVER

DRIVER’S SEAT	Ergo Metro AM384
DRIVER’S BARRIER	Arow Global ArowGuard MAX
STOP REQUEST	Pull cord
DASH DISPLAY	I/O Controls multi-function display
HEADLAMPS	I/O Controls DINEX™ STAR LED low beam / Hamsar® incandescent high beam
ADAS	Rosco® Mobileye® Shield+ V4.0™

ELECTRONICS

DESTINATION SIGNS	Hanover® full color
PASSENGER INFO	Hanover® w/ (2) 29” smart TFT monitors
VIDEO SURVEILLANCE	AngelTrax® 14-camera system
IT SYSTEM	Vontas OnRoute™ w/ integrated APC

Specifications reflect the PACE configuration and are subject to change.